

Ara



- Provides real-time CPU temperature, CPU speed and CPU load level
- Customized RGB lighting for UPS status
- Docking LCD design with Bluetooth communication
- Remote LCD panel is built-in 900mAH battery for 12-hour operating time
- Pure sine wave output
- Built-in AVR for voltage stabilization
- Built-in two USB charger ports for mobile devices
- Provides battery backup and surge protected outputs
- Easy replaceable battery design
- Built-in USB com. port and RJ-45 network surge protection
- Optional coax surge protection for TV antenna

Ara Line Interactive Sinewave Gaming UPS Selection Guide

MODEL	Ara 1000	Ara 1500
CAPACITY	1000 VA / 600 W	1500 VA / 900 W
INPUT		
Voltage	110/120 VAC or 220/230/240 VAC	
Voltage Range	81-132VAC/86-142VAC or 170-280VAC	
OUTPUT		
Voltage	110/120 VAC or 220/230/240 VAC	
AC Voltage Regulation (Batt. Mode)	±10%	
Frequency Range (Batt. Mode)	50/60 Hz ±1 Hz	
Transfer Time	6ms typical, 10ms max	
Waveform (Batt. Mode)	Pure Sine Wave	
BATTERY		
Battery Type & Number	12 V/9 Ah x 1	12 V/9 Ah x 2
Typical Recharge Time	6-8 hours recover to 90% capacity	
INDICATORS		
LCD Display	Input/output voltage, input/output frequency, load in VA/Watts, battery capacity, estimated remaining runtime, site wiring fault indications.	
USB CHARGER		
USB Charger Ports	Type C x 1 & Type A x 1	
Output Voltage	5.2V±5%	
Load Current	3A(MAX)	
PHYSICAL		
Dimension, D x W x H (mm)	308 x 99 x 280	430 x 99 x 280
Net Weight (kgs)	9.2	13.8
ENVIRONMENT		
Humidity	0-90 % RH @ 0- 40°C (Non-condensing)	
Noise Level	Less than 40dB	Less than 45dB
MANAGEMENT		
Optional USB Port	Supports Windows® 2000/2003/XP/Vista/2008/7, Linux, Unix, and MAC	
Compliance & Standards	110/120VAC model: cTUVus (standard:UL 1778), FCC Part 15 Class B, ENERGY STAR (USA) 220/230/240VAC model: CE , EN 62040-1:2008/A1:2013, IEC 62040-1:2008/A1:2013	

Product specifications are subject to change without further notice.